

Model 272

Remote Display/Annunciator

Radiation Detection for a Safer World



Ludlum Measurements, Inc.



Part No. 48-2656

Specifications

INDICATED USE: remote display/annunciator for the Model 375 series of Area Monitors

AUDIO: Sonalert-type speaker (greater than 68 dB at 0.61 m [2 ft]) with enable/disable switch

RADIATION READOUT DISPLAY: analog meter dial with 0.1mR/hr–10 R/hr logarithmic scale (others available)

STATUS INDICATORS:

OK: green LED

ALARM: red LED

FAIL: red LED

CONTROLS:

AUDIO: On/Off

REMOTE ALARM RELAY: Enable/Disable

ALARM RESET

POWER SUPPLIED BY: Model 375 instrument, 6.1 m (20 ft) cable provided (additional lengths available)

CONNECTOR: 9-pin connector

CONSTRUCTION: aluminum with ivory powder coat

TEMPERATURE RANGE: -20 to 50 °C (-4 to 122 °F), may be certified to operate from -40 to 65 °C (-40 to 150 °F)

SIZE: 22.9 x 12.7 x 10.9 cm (9 x 5 x 4.3 in.) (H x W x D)

WEIGHT: 0.9 kg (2 lb)

Alternate Instruments

Model 271: remote display/annunciator for the Model 375 series Digital Area Monitors, (Part No. 48-2475)

Model 271-2: dual channel remote display for Model 375 series Digital Area Monitors (Part No. 48-3536)

Model 272D: digital remote display/annunciator area monitor for the Model 375 series Digital Area Monitors, CE Certified (Part No. 48-3575)

P.O. Box 810, Sweetwater, Texas 79556 / <http://www.ludlums.com>

Tel: 800-622-0828 / 325-235-5494 / Fax: 325-235-4672 / Email: ludlum@ludlums.com

Sept 2013